

Manufacturer: **Hatteland Technology AS**

Product: **27 inch Maritime Multi Display (MMD)**

Type: **HD 27T27 MMD-MAX-UyGAA**

x = (1 No ECDIS) or 4 (ECDIS) y = A (No Bonding) O (Bonding)
H (HighBright Bonded), a = exp. board option (See factory option).

Last Revised: **08 Sep 2025**
Revision#: **10**

27 inch Maritime Multi Display - Series X G3


Features:

Series X Generation 3 (G3) displays offer the ultimate in performance, convenience, state of the art design and enduring quality for system integrators and boat builders. Series X products offer a range of feature sets optimized for varying requirements and applications.

The Series X Generation 3 (G3) display range is a flexible monitor solution designed and type approved for the professional maritime segment, where reliability and long life time are key prerequisites for the industry. The product range combines stunning design and technology with innovative features and options, making it all that the integrator needs for top class type-approved marine systems.

The multi-input MMD models provide a wide choice of display size and format for a multitude of shipboard applications, where combining data and video inputs to a single unit provides maximum flexibility. Be it for ship navigation, automation or security, this range with all it's possible options provides a robust and multipurpose platform from which to display and manage data and multiple camera or sensor videos.

Series X Generation 3 (G3) displays feature Glass Display Control, LED Backlight Technology, full dimming and multipower as standard, and can also accommodate and combine a number of options such as multi-touch screen, optical bonding and ECDIS calibration. By factory standards the 27 inch unit is ECDIS Compliant.



Dimensions might be shown with or without decimals and indicated as mm [inches]. Tolerance on drawings is +/- 1mm. For accurate measurements, check relevant DWG file.

TFT Technology:

- LED Backlight Technology, Color Active Matrix
- 27.0 inch viewable image size, Widescreen, Aspect Ratio 16:9
- a-SI (amorphous silicon) Thin Film Transistor (TFT)

TFT Characteristics:

- Native Resolution : 1920 x 1080 (FHD)
- Pixel Pitch (RGB) : 0.31125 (H) x 0.31125 (V) mm
- Response Time : 12 ms (typical) (on/off)
- Contrast Ratio : 3000:1 (typical)
- Light Intensity : 350 cd/m² (typical)
- Viewable Angle : +/- 89 deg. (typical) (Up/Down/Left/Right)
- Active Display Area : 597.6 (H) x 336.15 (V) mm
- Max Colors : 16.7 million

Supported Signals:**Resolutions:**

- VGA : 640 x 480 (including 640 x 350)
- SVGA : 800 x 600 (including 720 x 400)
- XGA : 1024 x 768
- SXGA : 1280 x 1024
- UXGA : 1600 x 1200
- FHD : 1920 x 1080*

* Recommended for optimal picture quality

Power Specifications:**Multi-power Supply:**

- 100-240V AC - 50/60Hz + 24 VDC

Note: You may connect either AC power or DC power or both. In case both sources are connected, power will be sourced from the AC input. If AC input is lost, there will be a uninterrupted switch-over to DC input.

Power Consumption:

- Operating AC/DC: 28W (Typ) 39W (Max)

Physical Considerations:**Product Carton Size and Weight:**

- W:621.00 [24.45"] x H:435.00 [17.13"] x D:82.50 [3.25"] mm [inch]
- Weight: Approx. 10.4kg / 22.9lbs
- Product Carton Size and Weight:**
- L:765.00 [30.12"] x W:190.00 [7.48"] x H:615.00 [24.21"] mm [inch]
- Weight: Approx. 13.2kg / 29.1lbs

Signal Terminals:

- DP 1.4 IN : 1 x 20p DisplayPort (female)*
- HDMI 2.0 IN : 1 x 19p HDMI (female)*
- USB-C : 1 x USB-C Female with DP 1.2 IN and USB2.0 (SCOM, touch and uC Firmware Update)*
- VGA/RGB IN : 1 x 15p D-SUB (female)*
- SCOM RS-422/485 : 2 x 5-pin Terminal Block 3.81, non-isolated+Buzzer
- SCOM Ethernet : 1 x RJ45 Connector
- SCOM RS-232 : 1 x 9p D-SUB (female)
- VS Firmware Update : 1 x USB TYPE A Connector (female)
- Potmeter/User : 1 x 9p D-SUB (male) (Potentiometer IN, +5VDC OUT, BRT +/- IN)
- AC Power IN : 1 x Std IEC Inlet
- DC Power IN : 1 x 2-pin Terminal Block 5.08

Note: Max Cable length: <2m*

User Controls:**Behind front bezel - Glass Display Control™ (GDC) IP66:**

- Power On/Off and On Screen Display Menu (OSD)*
 - Brightness Control (-/+)
 - Hotkeys (left/right), Mode Status Indicators (ECDIS)
 - Buzzer (through glass) (75-85dB), Light Sensor (behind glass)
- *OSD Key Codes: 321=Get access to OSD, 362=Advanced Mode

Environmental Considerations:

• Operating	: Temperature -15°C to +55°C
• Storage	: Temperature -30°C to +70°C
• Humidity	: Up to 95% (Operating / Storage)
• Shock - Vibration	: 5g/11ms - 0.7g (IEC 60945 / IACS E10)
• Air Pressure Maximum Altitude	: Operating: 4000m - Storage: 12912m
• Air Pressure Maximum Altitude (Bonded)	: Operating: 3000m - Storage: 3000m
• IP Rating	: Protection: IP66 front – IP22 rear (EN60529)
• Compass Safe Distance	: Standard: 50cm - Steering: 45cm

Lifetime Considerations:

Even though the test conditions for bridge units provide for a maximum operating temperature of 55°C, continuous operation of all electronic components should, if possible, take place at ambient temperatures of only 25°C. This is a necessary prerequisite for long life and low service costs.

Available Accessories:

- HD CMB SX2-E1 : 1 x Console Mount Kit. EN60945 Tested
- HD TMB SX1-C1 : 1 x Table Mount Bracket. EN60945 Tested
- HD VED SX2-K1 : 1 x VESA Adapter (100/100 & 200/100mm) Not EN60945 Tested
- HD REM SX1-A1 : 1 x External Remote Control, EN60945 Tested
- HD 27COV SX1-A1 : 1 x UV Sun Cover
- P018743 : 1 x IP66 Mount Gasket (EPDM), for Flush/Console mount
- HD CAK SX2-B1 : 1 x Front Console Mounting/Adapter Kit
- HT DPUSB-2-USBC-A1 : 1 x DP & USB2.0 (Male) to USB-C (Male) Adapter, 2m (not IP67)
- HT HDMIUSB-2-USBC-A1 : 1 x HDMI & USB2.0 (Male) to USB-C (Male) Adapter, 2m (not IP67)
- HT DVI-2-HDMI-A1 : 1 x DVI to HDMI Cable 2 meters
- HT DVI-2-HDMI-A2 : 1 x DVI to HDMI Cable 5 meters
- HT DVI-2-HDMI-A3 : 1 x DVI to HDMI adapter 0.2 meters

Factory Options:

- Optical Bonding Technology
- Color Calibrated models (ECDIS)
- Expansion board (DVI EXPcard 1xDVI IN)

APPROVALS & CERTIFICATES

These products have been tested / type approved by the following classification societies (* = Pending):

IEC 60945 4th (EN 60945:2002)
CCS - China Classification Society*

IACS E10
BV - Bureau Veritas

EU RO MR - Mutual Recognition by DNV
KR - Korean Register of Shipping

ClassNK - Nippon Kaiji Kyokai
ABS - American Bureau of Shipping